



MODEL	HP-012	HP-015	HP-108	HP-111	HP-114	HP-116
						
Moc (W35/W55)	7 / 8	14 / 15	8 / 7	11 / 10	14 / 13	16 / 17
SCOP (W35/W55)	4,30 / 3,30	4,26 / 3,32	4,55 / 3,41	4,62 / 3,44	4,67 / 3,45	4,60 / 3,46
Sterownik z panelem dotykowym	TAK	TAK	TAK	TAK	TAK	TAK
Kolorowy wyświetlacz	TAK	TAK	×	×	×	×
Aplikacja na telefon	×	×	TAK	TAK	TAK	TAK
Maksymalna temperatura na wyjściu	55	55	60	60	60	60
Czynnik	R410A	R410A	R32	R32	R32	R32
Zasilanie	220–240 V~ / 50 Hz	220–240 V~ / 50 Hz	220–240 V~ / 50 Hz	380–415 / 3 N / 50 Hz	380–415 / 3 N / 50 Hz	380–415 / 3 N / 50 Hz
Maksymalny pobór prądu	22	33	17	11	13	17
Waga	75	130	107	124	151	160
Wymiary	1005 × 375 × 800 mm	1025 × 380 × 1320 mm	1100 × 445 × 850 mm	1100 × 480 × 850 mm	1110 × 445 × 1450 mm	1110 × 445 × 1450 mm
Wbudowana pompa obiegowa	×	×	TAK	TAK	TAK	TAK